



## Declaration of Performance

67350050

305/2011/EU Construction Products Regulation

<b>1. Unique identification code of the product-type</b>	ISPOFLEX 50
<b>2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4).</b>	Printed on packaging
<b>3. Intended use or uses of the construction product, in accordance with the applicable harmonized technic specification, as foreseen by the manufacturer</b>	SEALANT FOR FACADE ELEMENTS : EN-15651-1: F-EXT-INT SEALANT FOR PEDESTRIAN WALKWAYS: EN-15651:PW-INT
<b>4. Manufacturer</b>	ISPO France 3, rue de Bitschhoffen 67350 LA WALCK France
<b>5. Authorized representative</b>	Not Relevant
<b>6. Systems of assessment of performance</b>	SYSTEM 3 ; SYSTEM 3 FOR REACTION TO FIRE
<b>7. Harmonized standard</b>	EN 15651-1 ; EN 15651-4
<b>8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued</b>	Not Relevant
<b>9 Notified Body</b>	4Ward Testing, NB 2538 has carried out the Determination of Product Type under system 3.

**Conditioning:** Method A

**Substrates:** Mortar 2  
Aluminium

<b>10. Declared Performance</b>			
<b>10</b>	<b>Essential Characteristic</b>	<b>Declared Performance</b>	<b>Harmonised Standard</b>
<b>10.1</b>	Reaction to fire	Class E	EN 15651-1:2012 EN 15651-4:2012
<b>10.2</b>	Release of Chemicals	NPD	
<b>10.3</b>	Water Tightness & Air Tightness as determined by :		
<b>10.3.1</b>	Resistance to flow	0 mm	

<b>10.3.2</b>	Loss of volume	≤6%	EN 15651-1:2012 EN 15651-4:2012
<b>10.3.3</b>	Tensile properties at maintained extension	NF	
<b>10.3.4</b>	Adhesion/Cohesion properties at maintained extension after water immersion	NF	
<b>10.3.5</b>	Elongation at break	≥ 25%	
<b>10.3.6</b>	Tear Resistance	NF	
<b>10.3.7</b>	Durability	Pass	

**10.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Note: this certificate is issued electronically and is valid without signature.

ISPO France  
Thomas MENDLER  
Manager

**Disclaimer :** The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, ISPO France gives no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.